



LED FLOODLIGHTS

BILLBOARDS • LANDSCAPES • AREA • PARKING LOTS



SPECIFICATIONS

- Die Cast Aluminum Housing
- Hinged Front Frame or Removable Back Cover for Easy Tool-less Access
- Textured Architectural Bronze Powdercoat Finish
- Dimple Textured Diffusive Tempered Glass Lens
- Watertight Cord Grip Installed
- Standard Yoke Included
- 4000K Color Temperature
- 5 Year Warranty
- DesignLights Consortium® Qualified

A Full Line for Every Application

Flood Series	Description	Lumens	Watts	Lm/W
FS-10WLED-UNIV-4000K	Small Flood with Yoke	887 lm	12W	77 lm/W
FMS-20WLED-UNIV-4000K	Medium Small Flood with Yoke	1,475 lm	19W	78 lm/W
FML-40WLED-UNIV-4000K	Medium Flood with Yoke	2,461 lm	35W	71 lm/W
FLL-60WLED-UNIV-4000K	Large Flood with Yoke	5,212 lm	62W	84 lm/W
FLL-80WLED-UNIV-4000K	Large Flood with Yoke	6,197 lm	76W	82 lm/W
FDL-100WLED-UNIV-4000K	Large Dual Flood with Yoke	9,117 lm	101W	90 lm/W
FDL-120WLED-UNIV-4000K	Large Dual Flood with Yoke	10,210 lm	118W	87 lm/W
FDL-140WLED-UNIV-4000K	Large Dual Flood with Yoke	13,760 lm	137W	100 lm/W
FDL-160WLED-UNIV-4000K	Large Dual Flood with Yoke	15,530 lm	160W	97 lm/W

All Configurations Listed on DLC.

Flood Mounting Options	FS	FMS	FML	FLL	FDL
Box Mount Adapter	Available	Available	Available	N/A	N/A
Tenon Mount Bracket	N/A	N/A	N/A	Available	Available
Pole Mount Bracket	N/A	N/A	N/A	Available	Available

LED Floodlight Series

These durable floodlights are perfect for a variety of outdoor lighting applications. The die cast aluminum housing has a hinged front frame on the 10W-80W, and a removable back cover on the 100W-160W models, for easy tool-less access to the internal driver, making installation and maintenance effortless.

Take Advantage of Our Special Stocking Dealer Program

Get better pricing, better freight terms, free samples, marketing material, and improved payment terms. Contact your ILP Sales Associate for details.

“Your Number One Source for Energy Efficient Lighting”

WWW.ILP-INC.COM



Contact ILP for More Information

Industrial Lighting Products
 519 Codisco Way
 Sanford, FL 32771
 ph: (407) 478-3759
 fax: (407) 478-3760