

SELECTION GUIDE



SKYLINE AREA LIGHT (SAS/SAM)

VIEWPOINT AREA LIGHT (VAS/VAM)

SUITABLE APPLICATIONS

PARKING LOT	✓	✓
CAR DEALERSHIP	✓	✓
PARKING STRUCTURE	✓	✓
DISTRIBUTION CENTER	✓	✓
EDUCATION	✓	✓
PARKS	✓	✓
ROADWAYS	✓	✓
RETAIL	✓	✓
HOSPITALITY	✓	✓
HOSPITAL	✓	✓

FEATURES & PERFORMANCE

LUMEN PACKAGES	Small: 6L, 9L, 12L, 15L, 18L Medium: 24L, 30L, 36L, 42L, 50L	Small: 14L, 17L, 21L Medium: 21L, 24L, 28L or 33L, 37L, 42L
EFFICACY (lm/W) UP TO	165 LPW	162 LPW
LUMEN SELECTABLE	Optional with FAO	✓
ROTATABLE OPTICS	✓	✓
CCT OPTIONS	3K, 4K, 5K	4K, 5K
DISTRIBUTIONS	T2, T3, T4, T5S, FTA (Forward Throw Automotive), Flood - Medium, Wide, Very Wide + Back Light Control	T3, T4, T5
VOLTAGE	120-277V, 347-480V	120-277V, 277-480V
MOUNTING OPTIONS	Fixed Pole Mount, Adj. Pole Mount, Adj. Slip Fitter, Mast Arm, Fixed Wall Mount, Adj. Wall Mount, Trunnion + Round Poles	Adjustable Pole, Slip Fitter, Wall Mount and Surface Mount Box
FINISHES	Black, White, Silver, Bronze & Custom Color	Bronze Standard; Upcharge for Black, White, Silver & Custom Color
DISTRIBUTION PERFORMANCE	Very High Spacing & Uniformity	Intermediate Spacing & Uniformity
SURGE PROTECTION	6kV Standard, Optional 10kV & 20kV	4kV Standard, Optional 10kV & 20kV
LIFE	L82>100k hours	L70>100k hours
AMBIENT RANGE	-40° to +50°C	-40° to +50°C
IP RATINGS	IP66	IP66
BAA COMPLIANT	✓	
DLC	Premium	Premium

BASIC CONTROLS

CONTROL RECEPTACLE	3-Pin or 7-Pin	3-Pin or 7-Pin
PHOTOCELL	Twist lock	Twist lock
FIELD ADJUSTABLE OUTPUT (FAO)	✓	
OCCUPANCY SENSOR	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor

ADVANCE GROUPING CONTROLS

ENLIGHTED	Integral or via control receptacle	Via Control Receptacle Only
SYNAPSE	Integral or via control receptacle	Via Control Receptacle Only
LEVITON	✓	✓