

SELECTION GUIDE



UFO PARKING GARAGE (UFO)

SQUARE CANOPY (CP)

SUITABLE APPLICATIONS

	UFO	CP
PARKING GARAGE	✓	✓
CANOPY	✓	✓
ENTRANCE WAY	✓	✓
LOW BAY	✓	
WALKWAYS	✓	✓
LOADING DOCKS	✓	✓
STAIRWAYS	✓	✓
CAR PORTS	✓	✓
BUILDING PERIMETER	✓	✓

FEATURES & PERFORMANCE

LUMEN PACKAGES	3L-9L	3L-9L
LPW (UP TO)	146 LPW	134 LPW
CRI	>80	>80
CCT OPTIONS	3K, 4K, 5K	4K
DISTRIBUTIONS	Wide & Narrow (Low Bay)	Wide & Medium
UPLIGHT (UP TO)	10% Standard	3% Standard
VOLTAGES	120-277V or 347-480V	120-277V or 347-480V
HOUSING	Round	Square
LENSING	Diffuse Polycarbonate	Diffuse Medium or Parking Garage Wide Polycarbonate Lenses
MOUNTING	Quick Surface Mount, Pendant, Trunnion	Quick Surface Mount, Pendant
BIRD CONE SHIELD	✓	
BATTERY BACKUP	6W-14W Cold Temp -4°F to -40°F	5W-12W Cold Temp -4°F to -40°F
SURGE PROTECTION	6kV	2.5kV
LED LIFETIME	L70 > 100K	L70 > 50K
AMBIENT RANGE	-40 to +50°C	-40 to +40°C
RATINGS	IP66	IP65
BAA COMPLIANT	✓	
FINISHES	Bronze, Black, White, Silver & Custom Color	Bronze or White Standard
DLC	Standard & Premium	Premium

BASIC CONTROLS

PHOTOCELL	Electronic Pencil Photocell	Electronic Pencil Photocell
OCCUPANCY SENSOR	Field Adjustable Bluetooth Programmable Sensor	Microwave or Drop Nipple Field Adjustable Bluetooth Programmable Sensor

ADVANCE GROUPING CONTROLS

ENLIGHTED	Integrated	
SYNAPSE	Integrated	