

SELECTION GUIDE

	SKYLINE FLOOD (SFS/SFM)	VIEWPOINT FLOOD SERIES (VFC/VFS/VFM/VFL/VFX)	CONVERTAFLOOD (CFS/CFM)
SUITABLE APPLICATIONS	AREA LIGHTING	✓	✓
	LANDSCAPE		✓
	FLAG POLE		✓
	WALL WASH		✓
	SIGNAGE		✓
	ELEVATION ILLUMINATION		✓
	CANOPY LIGHTING		✓
	FACADE LIGHTING		✓
	GENERAL PURPOSE	✓	✓
	PERIMETER SITE LIGHTING	✓	✓
	HOUSING SIZES	2	5
LUMEN PACKAGES	Small: 6L-18L Medium: 24L-50L	Compact: 2L Small: 5L-7L Medium: 10L-14L Large: 20L-30L Extra Large: 40L	Small: 4L Medium: 6L-10L
LPW (UP TO)	165 LPW	159 LPW	130 LPW
LUMEN SELECTABLE	Optional with FAO	4 Fixed Levels per Lumen Package	Rotary Knob Continuous Adjustability
CRI	>70	>70	>80
CCT OPTIONS	3K, 4K, 5K	3K, 4K, 5K, CCT Selectable	4K, 5K
DISTRIBUTIONS	Medium, Wide Forward Throw, Very Wide	Medium or Wide	3x3, 4x4, 5x5, 7x6
VOLTAGES	120-277V or 347-480V	120-277V or 277-480V	120-277V
MOUNTING	Adjustable Pole Mount, Adjustable Slip Fitter, Adjustable Wall Mount, Trunnion	Knuckle, Knuckle with Tenon Adapter, Adjustable Slip Fitter, Pole Mount, Surface Mount Box	Knuckle, Knuckle with Tenon Adapter, Trunnion
SURGE PROTECTION	6kV	6kV (VFC 2.5kV)	2.5kV
LED LIFETIME	L82 > 100K	L70 > 100K	L70 > 100K
AMBIENT RANGE	-40 to +50°C	-40 to +50°C (VFL-30L +45°C)	-40 to +50°C
RATINGS	IP66	IP66	IP66
BAA COMPLIANT	✓		
FINISHES	Bronze, Black, White, Silver & Custom Color	Bronze Standard; Upcharge for Black, White, & Silver	Bronze, Black & White
DLC	Premium	Premium	Unlisted
BASIC CONTROLS	PHOTOCELL	Electronic Pencil Photocell	Embedded Electronic Photocell
	FAO (FIELD ADJUSTABLE OUTPUT)	Optional	✓
	OCCUPANCY SENSOR	Field Adjustable Bluetooth Programmable Sensor	
ADVANCE GROUPING CONTROLS	ENLIGHTED	Integrated	Via Control Receptacle
	SYNAPSE	Integrated	Via Control Receptacle