



STRIPS

COMMERCIAL

SELECTION GUIDE

STRIPS SELECTION GUIDE

	DISCOVERY (DSC)	QWIKLINK LINEAR STRIP (QL)	VS STRIP 3.0 (VS)	SS STRIP 3.0 (SS)
SUITABLE APPLICATIONS	EDUCATION	✓	✓	✓
	HEALTHCARE	✓	✓	✓
	COMMERCIAL OFFICE	✓	✓	✓
	RETAIL	✓	✓	✓
	STORAGE FACILITY	✓	✓	✓
	GROCERY STORE	✓	✓	✓
	RESIDENTIAL	✓	✓	✓
	INDUSTRIAL	✓	✓	✓
FEATURES & PERFORMANCE	LUMEN RANGE	2,000 - 17,000	1,200 - 5,200 (Lumen Selectable)	2,000 - 12,000
	EFFICACY (lm/W) UP TO	169	130	162
	CRI	>80	>80	>80
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40 (CCT Selectable)	35, 40, 50
	VOLTAGE	120-277V - Opt. 347-480V	120-277V	120-277V - Opt. 347-480V
	DIMMING RANGE	100%-10% standard (1% Dim Opt)	100%-10%	100%-10%
	AMBIENT RANGE	-4°F - 120°F	-4°F - 131°F	-4°F - 122°F
	SIZES	2FT, 4FT & 8FT	2FT & 4FT	2FT, 4FT & 8FT
	WIDTH	4.3"	2.5"	2.8"
	LENS STYLE	Flat	Flat	Round
	MOUNTING	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended	Continuous Run, Pendant, Surface, Suspended, Wall
	SENSOR MOUNTING	Integral & End	End	End
	RATINGS	Damp, ETL	Damp, ETL	Damp, ETL
	DLC	Standard & Premium	Standard & Premium	Standard
	BASIC CONTROLS	BAA COMPLIANT	✓	
BABA COMPLIANT		✓		
RETROFIT KIT OPTION		✓		
ON/OFF OCCUPANCY		✓	✓	✓
DAYLIGHT HARVESTING		✓	✓	✓
BI-LEVEL OCCUPANCY		✓	✓	✓
BI-LEVEL OCCUPANCY WITH PHOTOCELL		✓	✓	✓
ADVANCE GROUPING CONTROLS		EASYSENSE	✓	
	ENLIGHTED	✓		
	LUTRON	✓		