

SELECTION GUIDE

	VAPOR TIGHT RETROFIT (VTR)	VAPOR TIGHT HIGH BAY RETROFIT (BLR)		
SUITABLE APPLICATIONS	COOLERS & FREEZERS	✓	✓	
	FOOD & BEVERAGE PREPARATION	✓	✓	
	GREENHOUSE	✓	✓	
	PHARMACEUTICAL	✓	✓	
	HEALTHCARE	✓	✓	
	EDUCATION	✓	✓	
	INDUSTRIAL	✓	✓	
	HOCKEY RINKS		✓	
	SAW MILLS	✓	✓	
FEATURES & PERFORMANCE	LUMEN RANGE	2,000 - 13,000	12,000 - 30,000	
	EFFICACY (lm/W) UP TO	155	154	
	CRI	>80	>80	
	CCT OPTIONS	30, 35, 40, 50	30, 35, 40, 50	
	DISTRIBUTION	Wide	Wide & Narrow	
	VOLTAGE	120-277V - Opt. 347V, 480V	120-277V - Opt. 347V, 480V	
	SIZES	4FT & 8FT	4FT	
	HOUSING	Linear	Linear	
	LENSING (OPTIONAL)	Clear & Frosted Acrylic, Clear & Frosted Polycarbonate	Clear & Frosted Acrylic, Clear & Frosted Polycarbonate	
	LIFE (L70)	>100K	>100K	
	AMBIENT RANGE	-40°F - 115°F (96W to 110°F)	-40°F - 130°F (160W to 125°F)	
	EMERGENCY	✓	✓	
	BAA COMPLIANT	✓	✓	
	DLC	Standard	Premium	
	BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓
		ON/OFF OCCUPANCY W/ PHOTOCCELL	✓	✓
BI-LEVEL OCCUPANCY		✓	✓	
BI-LEVEL OCCUPANCY W/ PHOTOCCELL		✓	✓	