



# WALL PACKS

## OUTDOOR

### SELECTION GUIDE



### WALL PACKS SELECTION GUIDE

	SKYLINE WALL PACK (SWx)	VIEWPOINT WALL PACK (VWM)	SKYLINE WALL MOUNT (SAS/SAM)	SLIM WALL PACK (SWP)	OW SERIES WALL PACK (OWS, OWM, OWL)	
SUITABLE APPLICATIONS	PEDESTRIAN WALKWAYS	✓	✓	✓	✓	
	BUILDING ENTRANCES	✓	✓	✓	✓	
	MULTI-USE FACILITIES	✓	✓	✓	✓	
	PARKING LOTS	✓	✓	✓	✓	
	STORAGE FACILITIES	✓	✓	✓	✓	
	INSTITUTIONS	✓	✓	✓	✓	
	SCHOOLS	✓	✓	✓	✓	
	LOADING DOCKS	✓	✓	✓	✓	
	WAREHOUSES	✓	✓	✓	✓	
	SHOPPING CENTERS	✓	✓	✓	✓	
HOUSING SIZES	3	1	2	2	3	
LUMEN PACKAGES	Small: 1L-3L Medium: 3L-12L, Large: 12L-24L	Medium: 3L-14L	Small: 6L-18L Medium: 24L-50L	Small: 2L-3L Medium: 5L-10L	Small: 1L-4L Medium: 3L-5L, Large: 5L-16L	
LPW (UP TO)	160LPW	147 LPW	165 LPW	150 LPW	147 LPW	
LUMEN SELECTABLE	No	✓	Optional with FAO	Optional with FAO	✓	
CRI	>80	>70	>70	>70	>70	
CCT OPTIONS	3K, 4K, 5K	3K, 4K, 5K CCT Selectable	3K, 4K, 5K	3K, 4K, 5K CCT Selectable	3K, 4K, 5K CCT Selectable	
DISTRIBUTIONS	T2, T3, T4, T4FT	T3, T4	T2, T3, T4, FTA	T4	T4	
DISTRIBUTION PERFORMANCE		Moderate Uniformity and Targeted Performance	Excellent Uniformity and Targeted Performance	Low Uniformity and Targeted Performance	Low Uniformity and Targeted Performance	
IDA	✓	✓	✓	IDA Option	Optional	
VOLTAGES	120-277V or 347-480V	120-277V or 277-480V	277-480V	120-277V or 277-480V	120-277V or 277-480V	
MOUNTING	Bracket with No Through Drilling, optional Standard Back Box and Architectural Wall Spacer	Drill Through Back Casting	Bracket with No Through Drilling	Bracket with No Through Drilling	Drill Through Back Casting	
BATTERY BACKUP	EM5, EMCT6, EMCT8, EMCT14, EM16	14W, 14W Cold Temp (-4°F), 8W Cold Temp (-22°F), 6W Cold Temp (-40°F)		Both 14W. Cold temp to -4°F	Small: N/A; Medium/Large: 5W-10W, 10W Cold Temp (-4°F), 8W Cold Temp (-22°F), 6W Cold Temp (-40°F)	
SURGE PROTECTION	Surge Protection -10kA:1L-4L; 6kV 6L-24L; 10kV; 20kV	6kV	6kV	2.5kV	6kV (2.5kV OWS)	
LED LIFETIME	L85 > 100K	L70 > 100K	L82 > 100K	L70 > 100K	L70 > 100K	
AMBIENT RANGE	-40 to +50°C	-40 to +40°C	-40 to +50°C	-40 to +40°C	-40 to +45°C	
RATINGS	IP66	IP65	IP66	IP65	IP65	
BAA COMPLIANT	✓		✓			
FINISHES	Bronze, Black, White, Silver, Natural Aluminum; Upcharge for Custom Color	Bronze Standard, Upcharge for Black, White, Silver, Natural Aluminum & Custom Color	Bronze, Black, White, Silver; Upcharge for Natural Aluminum & Custom Color	Bronze Standard; Upcharge for Black, White, Silver, Natural Aluminum & Custom Color	Bronze Standard; Upcharge for Black, White, Silver, Natural Aluminum & Custom Color (OWM/OWL)	
DLC		Premium	Premium	Premium	Premium	
ADVANCE BASIC GROUPING CONTROLS	PHOTOCELL	Electronic Button Photocell	Electronic Pencil Photocell	3/7-Pin Control Receptacle	Electronic Pencil Photocell	Electronic Pencil Photocell
	FAO (FIELD ADJUSTABLE OUTPUT)			7 Levels	7 Levels	
	OCCUPANCY SENSOR	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	Field Adjustable Bluetooth Programmable Sensor	External Field Adjustable Bluetooth Programmable Sensor
	NUROAir	Integrated		Integrated or via control receptacle		
	SYNAPSE	Integrated		Integrated or via control receptacle		

