



WRAPS

COMMERCIAL

SELECTION GUIDE



WRAPS SELECTION GUIDE

	SWR UTILITY WRAP (SWR)	CURVED WRAP & CURVED WIDE BASE WRAP (SQ & SQ-WB)	FNW LED NARROW WRAP & FWW LED WIDE WRAP (FNW & FWW)	
SUITABLE APPLICATIONS	EDUCATION	✓	✓	
	HEALTHCARE	✓	✓	
	COMMERCIAL OFFICE	✓	✓	
	STORAGE FACILITY	✓	✓	
	WAREHOUSE	✓	✓	
	WORKSTATION/TASK	✓	✓	
	HALLWAY	✓	✓	
	MULTIPURPOSE	✓	✓	
FEATURES & PERFORMANCE	LUMEN RANGE	1,800 - 6,000	3,000 - 10,000	2,000 - 8,000
	EFFICACY (lm/W) UP TO	122	129	132
	CRI	>80	>80	>80
	CCT OPTIONS	35, 40, 50	30, 35, 40, 50	35, 40, 50
	VOLTAGE	120-277V	120-277V - Opt. 347-480V	120-277V - Opt. 347-480V
	DIMMING RANGE	100%-10% Standard (1% Dim Opt)	100%-10% Standard (1% Dim Opt)	100%-10% Standard (1% Dim Opt)
	AMBIENT RANGE	-4°F - 104°F	-4°F - 130°F	-4°F - 114°F
	SIZES	2FT & 4FT	2FT, 4FT & 8FT	4FT & 8FT
	WIDTH	5.4" Standard	5.8" Standard (12" with -WB Option)	8.8" Standard (13.3" with FWW Models)
	LENS STYLE	Frosted Polycarbonate	Curved, Frosted Acrylic	Curved, Frosted Acrylic
	MOUNTING	Surface, Suspended, JBox & FMB	Surface, Suspended, Continuous Row	Surface, Suspended, Continuous Row
	SENSOR MOUNTING	Integral	Integral & End	End
	RATINGS	ETL	Damp, ETL	Damp, ETL
	DLC	Standard	Standard	Standard
BAA COMPLIANT		✓	✓	
BABA COMPLIANT		✓	✓	
BASIC CONTROLS	ON/OFF OCCUPANCY	✓	✓	✓
	DAYLIGHT HARVESTING	✓	✓	✓
	BI-LEVEL OCCUPANCY	✓	✓	✓
	BI-LEVEL OCCUPANCY WITH PHOTOCELL	✓	✓	✓
ADVANCE GROUPING CONTROLS	EASYSense		✓	
	ENLIGHTED		✓	✓
	LUTRON		✓	